



| PARTS LIST | | |
|---------------|---|-----|
| PART NUMBER | DESCRIPTION | QTY |
| 16 | SMOKE DOME-60/72" | 2 |
| 18 | SMOKE DOME-72" | 2 |
| 21 | BASEPLATE-36" | 2 |
| 34 | SMOKE DOME SIDE | 2 |
| 69 | DAMPER BEAM-42" | 2 |
| 72 | BACKWALL 60/72" | 3 |
| 73 | BACKWALL-72" | 3 |
| 77 | TOP PLATE-36/42" | 1 |
| 83 | DAMPER BEAM-72" | 2 |
| 121 | TOP PLATE-82L72 | 2 |
| M90 | MAGNUM SIDEWALL | 4 |
| M90B | GLASS FRONT KIT SIDEWALL | 2 |
| M91 | MAGNUM BASE PLATE-36" | 2 |
| M94L | MAGNUM DAMPER BLOCK; LEFT | 1 |
| M94R | MAGNUM DAMPER BLOCK-RIGHT | 1 |
| E-ACB-A | Air Collector Box A | 2 |
| CG2 | NEOCERAM GLASS-GFK72 | 3 |
| ISF60LB | 60" LINEAR BURNER ASSEMBLY | 1 |
| 12MDD | METAL- FAB 12" B-VENT DOWN DRAFT DIVERTER | 1 |
| OAK12NG | 4" COOLING AIR KIT | 2 |
| 302.0100.1200 | ADC 100 W/ PDS | 1 |
| 216.0100.1212 | ENERVEX 12" MFD FOR RS012 FAN | 1 |
| 101.0499.1200 | ENERVEX RS012 | 1 |
| N/A | 6"x6"x1/2" STEEL ANGLE (NOT PROVIDED BY EARTHCORE, MUST SOURCE LOCALLY) | 1 |
| E-TG2 | TOP GLASS BRACKET ASSEMBLY | 3 |

- GENERAL NOTES:**
1. THE ISOKERN LINEAR FIREPLACE MODELS ARE TOP-VENTED, GAS ONLY FIREPLACES THAT ARE LISTED FOR USE ONLY WITH THE ISOKERN MODULAR BURNER SYSTEM AS SHOWN IN THESE DRAWINGS AND LISTED IN THE INSTALLATION MANUAL. THESE GAS APPLIANCES COME WITH A GAS CONTROL VALVE ASSEMBLY THAT INCLUDES AN AUTOMATIC DRAFT AND SAFETY SYSTEM.
 2. THIS APPLIANCE IS ONLY FOR USE WITH THE TYPE OF GAS INDICATED ON THE RATING PLATE AND MAY BE INSTALLED IN THE AFTER-MARKET, PERMANENTLY LOCATED, MANUFACTURED HOME (USA ONLY) OR MOBILE HOME, WHERE NOT PROHIBITED BY LOCAL CODES. SEE OWNER'S MANUAL FOR DETAILS.
 3. THE EXHAUST FLUE GASES ARE TO BE VENTED THROUGH THE TOP OF THE UNIT WITH 12" METAL-FAB UL LISTED B-VENT PIPING WITH DOWN-DRAFT DIVERTER. THIS TWELVE INCH (12") DIAMETER, DOUBLE WALL B-VENTING SYSTEM ARE NOT SUPPLIED BUT ARE REQUIRED FOR PROPER OPERATION OF ALL LINEAR FIREPLACE MODELS.
 4. GLASS FRONT KIT ASSEMBLY SHALL BE INSTALLED AS DETAILED IN THE INSTRUCTION MANUAL.
 5. NOT REPRESENTED ON THIS DRAWING, BUT MANDATORY FOR OPERATION ARE (2X) Ø4" COOLING AIR KITS. THESE SHALL ORIGINATE FROM OUTSIDE AIR ARE UTILIZED TO PROVIDE COOLING AIR TO THE GLASS.
 6. DRAWINGS ARE FOR DESIGN PURPOSES ONLY AND ARE THE SOLE PROPERTY OF EARTHCORE INDUSTRIES. ANY REPRODUCTION OR UNAUTHORIZED USE IS STRICTLY PROHIBITED.
 7. EARTHCORE/ ISOKERN OR ANY DIVISION THEREOF SHALL NOT BE HELD LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR EXPENSES ARISING OUT OF THE USE OF THE FIREPLACES OR CHIMNEY SYSTEMS.
 8. ALWAYS CHECK LOCAL BUILDING CODES GOVERNING FIREPLACES AND FIREPLACE INSTALLATIONS.

earthcore INDUSTRIES, L.L.C.

UNLESS OTHERWISE STATED, ALL DIMENSIONS ARE IN INCHES

PROJECT: **6' MAXIMUS LINEAR W/ GFK**

DESCRIPTION: **FIREPLACE CONSTRUCTION DOCUMENT**

MATERIAL: **E.C. PUMICE MIXTURE**

DRAWN: **K.B.H.** DATE: **5/20/20**

APPROVED: **[Signature]** DATE: **5/20/20**

SIZE: **D** SCALE: **1"=1'-0"** DRAWING #: **82L72-GFK** REV: **01**

DO NOT SCALE SHEET # OF